

VICA

POWER GENERATION

Powered by Air Cooled Hatz Diesel Engine
3000rpm



Genset Model	Output kW	Output kVA	Engine Model	Dimensions (mm)			Weight kg
				Length	Width	Height	
VC02500H	2.0	2.5	1B20	660	360	400	48
VC04000H	3.5	4.4	1B30	700	370	430	56
VC05000H	4.0	5.0	1D41	750	470	530	72
VC06000H	5.0	6.3	1B40	740	400	480	80
VC07000H	5.5	6.9	1D50	770	470	530	110
VC09500H	7.5	9.4	1D81	780	510	620	136
VC10000H	8.0	10.0	1D90	780	510	620	160
VC12500H	10.0	12.5	2G40	780	510	620	160

We reserve the right to change this specification without notice.

For more detailed information concerning individual models please contact VICA Power.

Standard Equipment consists of:

Hatz Diesel Engine
The Alternator with AVR
Engine Driven Battery Charging System
Robust Fabricated Steel Base Frame
Industrial Silencer
Flexible Exhaust Section
Rubber Anti-Vibration Mounts
Plant Mounted Control System
Circuit Breaker
12 or 24 V Lead Acid Battery(s) and Leads

Standard Options Available:

Manual Key Switch Start Control Panel
Semi-Automatic Mains Failure Control System
ATS Panel (Full Automatic Start)
Engine Heater to Aid Cold Start
Residential Silencer
Integral Base Fuel Tank
Weatherproof and Acoustic canopies

Ratings:

Ratings quoted represent the normal engine and alternator performance capabilities, guaranteed within plus or minus 5% at NTP conditions, in accordance with ISO 3046, BS5514 and DIN 6271.

Standby Power:

Suitable for supplying electrical power (at variable load) in the event of a utility power failure but no overload is permitted.

Please consult your distributor or the factory for rating in other ambient conditions.

Fuel:

Diesel fuel conforming to BS 2869: Class A1/2 and ASTM D975, 66T number 1D or 2D.



VICA Power Limited
22 Heath Green Way,
Coventry,
CV4 8GU
England

VICA Power Plant
Wakerley Works,
Bourne Road, Essendine,
Stamford, Lincs, PE9 4LR
England

Telephone: +44 (0) 24 7647 0870
Fax: +44 (0) 24 7646 5534
email: sales@vica.co.uk
Website: www.vica.co.uk

VICA

POWER GENERATION

Powered by Air Cooled Lombardini Diesel Engine
3000rpm



Genset Model	Output kW	Output kVA	Engine Model	Dimensions (mm)			Weight kg
				Length	Width	Height	
VC02500L	2.0	2.5	15LD225	600	360	420	49
VC03500L	3.0	3.8	15LD315	690	380	450	56
VC04500L	3.5	4.3	15LD350	740	400	480	65
VC05000L	4.0	5.0	6LD400	790	430	500	79
VC05500L	4.5	5.6	15LD400	730	400	480	80
VC06000L	4.8	5.9	6LD435	790	430	500	82
VC06500L	5.0	6.2	15LD440	730	400	480	85
VC07000L	5.6	7.0	3LD510	850	400	480	120
VC10000L	8.0	10.0	7LD665	890	470	600	140
VC12500L	10.0	12.5	12LD435-2	1100	520	550	180
VC15000L	12.0	15.0	12LD475-2	1100	520	550	185
VC18000L	15.0	18.8	9LD625-2	1100	560	600	210
VC27500L	22.0	27.5	11LD626-3	1220	680	690	270

We reserve the right to change this specification without notice.

For more detailed information concerning individual models please contact VICA Power.

Standard Equipment consists of:

Lombardini Diesel Engine
The Alternator with AVR
Engine Driven Battery Charging System
Robust Fabricated Steel Base Frame
Industrial Silencer
Flexible Exhaust Section
Rubber Anti-Vibration Mounts
Plant Mounted Control System
Circuit Breaker
12 or 24 V Lead Acid Battery(s) and Leads

Standard Options Available:

Manual Key Switch Start Control Panel
Semi-Automatic Mains Failure Control System
ATS Panel (Full Automatic Start)
Engine Heater to Aid Cold Start
Residential Silencer
Integral Base Fuel Tank
Weatherproof and Acoustic canopies

Ratings:

Ratings quoted represent the normal engine and alternator performance capabilities, guaranteed within plus or minus 5% at NTP conditions, in accordance with ISO 3046, BS5514 and DIN 6271.

Standby Power:

Suitable for supplying electrical power (at variable load) in the event of a utility power failure but no overload is permitted.

Please consult your distributor or the factory for rating in other ambient conditions.

Fuel:

Diesel fuel conforming to BS 2869: Class A1/2 and ASTM D975, 66T number 1D or 2D.



VICA Power Limited
22 Heath Green Way,
Coventry,
CV4 8GU
England

VICA Power Plant
Wakerley Works,
Bourne Road, Essendine,
Stamford, Lincs, PE9 4LR
England

Telephone: +44 (0) 24 7647 0870
Fax: +44 (0) 24 7646 5534
email: sales@vica.co.uk
Website: www.vica.co.uk